

Technical data sheet

TH620 (GL-V)

Thinner/smoothing agent for system components

Areas of application

- System thinner for indicated products
- Smoothing agent for trowels

See primer recommendations:
REVOPUR® (TL35)

Properties

- Colour shade: Colourless

Coverage

Depending on how it is applied

Delivery form

- 3 l Tin canister
- 1 l Tin bottle

Storage

Store in original container at +5°C to +30°C in a dry place.
Avoid containers coming into contact with direct sunlight, even on the construction site.
Can be stored for 36 months after production.


Processing

Application

The thinner is added to the system products according to the prescribed quantity and stirred in thoroughly.

The smoothing agent is spread out evenly using a brush on the trowel as required.

Tools and aids



Personal protective equipment

Please consult the product safety data sheet for information on personal protective equipment.

General information

The product must not be mixed and processed with other substances not belonging to the system. No materials other than those specified by FRANKEN SYSTEMS GmbH are permitted to be used.

Miscellaneous

It's to the best of our knowledge that we've provided the above information as well as our technical advice on applications,



Additional product

whether verbal, in writing or by means of tests. However, this information shall only be regarded as non-binding, which also applies to any property rights of third parties. The advice does not release you from examining our current advisory notes yourself (our safety data sheets and technical information in particular) and our products with regard to their suitability for the intended processes and purposes. The application, use and processing of our products as well as the intended use selected by you on the basis of our technical application-specific advice are beyond our control and are therefore exclusively your responsibility. The sale of our products is subject to our current General Terms and Conditions of Sale and Delivery. Warnings on the product labels must be observed. The latest version of the applicable documents shall be used.

Please check that the documents used are up-to-date and/or request an up-to-date document before each application.