

Technical data sheet

Vlies

Fleece 165 g/m²

Areas of application

Vlies is a high-quality polyester fleece as a layer thickness control and for reinforcing FRANKEN SYSTEMS waterproofing products with a fleece insert

Features

- Ready to use

Properties

- Weight per m²: approx. 165 g/m² ± 10 g/m²
- Colour shade: White

Coverage

1 m²/m²

Fleece overlaps must be taken into account

Delivery form

- Roll 10 cm x 60 m
- Roll 15 cm x 60 m
- Roll 20 cm x 60 m
- Roll 25 cm x 60 m
- Roll 30 cm x 60 m
- Roll 35 cm x 60 m
- Roll 50 cm x 60 m
- Roll 75 cm x 60 m
- Roll 100 cm x 60 m

Storage

Protect from damp, store upright and without kinks.

Processing

Application

The fleece cut with the scissors is worked into the fresh seal without creases or voids.

Multiple overlapping areas must be sufficiently soaked in the individual layers with the sealant. The overlapping areas of the subsequent fleece layers must be designed with a minimum width of 5 cm.

Tools and aids



Scissors

General information

No materials other than those specified by FRANKEN SYSTEMS GmbH are permitted to be used.



Polyester fleece

Miscellaneous

It's to the best of our knowledge that we've provided the above information as well as our technical advice on applications, whether verbal, in writing or by means of tests. However, this information shall only be regarded as non-binding, which also applies to any property rights of third parties. The advice does not release you from examining our current advisory notes yourself (our safety data sheets and technical information in particular) and our products with regard to their suitability for the intended processes and purposes. The application, use and processing of our products as well as the intended use selected by you on the basis of our technical application-specific advice are beyond our control and are therefore exclusively your responsibility. The sale of our products is subject to our current General Terms and Conditions of Sale and Delivery. Warnings on the product labels must be observed. The latest version of the applicable documents shall be used.

Please check that the documents used are up-to-date and/or request an up-to-date document before each application.