Trapac® Safety Hook





Klöber's installation instructions should be followed closely when fitting this product.

Trapac® Safety Hooks are for fixing loads such as roofers' ladders in place while work is being carried out on the roof. They are available in three versions to suit slate and profiled concrete and clay tiles and plain tiles.

Product features & benefits

- Quick & easy to install
- Corrosion-resistant galvanised and powder coated
- The hook's 45mm offset for concrete and clay tiles allows it to be easily fitted to the rafter
- Special fixing screws included
- Safety equipment can also be hung on the eyelet
- Suitable to carry loads in the direction of the roof's fall line

Area of application

Suitable for:

- Most clay & concrete interlocking tiles & slates
- New build & refurbishment

Material

Galvanised steel 30 x 6mm; S 235 J2 G3C according to DIN EN 10025

Packaging

10 pieces per carton including 32 nails

Colour codes

Red -0100 Galvanised -0370 Anthracite -0430

Regulations

- CE-certified
- Complies with DIN EN 517 Type A for loads in the direction of the roof's fall-line

TECHNICAL DATA	C€		
Coating	galvanised or galvanized and powder coated		
Versions	for tiles	for slate	for plain tiles
	45 mm cranked		30 mm cranked
Sketch			
Weight	ca. 1,18 kg / p.	ca. 1,0 kg / p.	ca. 1,14 kg / p.
Product code	KS 9000	KS 9001	KS 9002

TS-01#06-EN-1012. Für Druckfehler wird keine Haftung übernommen. ®Eingetragenes Warenzeichen der Klöber GmbH.

