

(DoP: 201)

Declaration of performance

Construction Products Regulation (EU) No 305/2011

1. Product:	Classics EPDM, Classics EPDM Kleen, Classics EPDM pre-tape.
2. Product Identification:	See bar code and label on packaging.
3. Intended Use:	Flexible membranes for water waterproofing, EN 13956
4. Manufacturing Locations:	VM Building Solutions NV/SA Schoonmansveld 48 B-2870 Puurs-Sint-Amands
5. Representative Contact:	N.A.
6. AVCP:	2+
7. Notified Body (hEN):	BCCA Hermeslaan 9, 1831 BE-Diegem Registration No. 0749
8. Notified Body (ETA):	N.A.

9. Declared Performance:			
Essential Characteristics	Performance	Test standard	Harmonised technical specifications
Effective Thickness	-5% to +10%	EN 1849-2	EN 13956: 2012
External Fire Performance	F _{roof} ¹	EN 13501-5	
Reaction to Fire	E	EN 13501-1	
Joint Peel Resistance (N/50mm)	≥ 25	EN 12316-2	
Joint Shear Resistance (N/50mm)	≥ 200	EN 12317-2	
Tensile (Breaking) Strength (N/50mm)	≥ 350	EN 12311-2	
Elongation (%)	≥ 15		
Tear Resistance (N)	≥ 25		
Dimensional Stability (%)	≤ 0,5	EN 1107-02	
Flexibility at Low Temperature (°C)	≤ -45	EN 495-5	
UV Exposure	pass	EN 1297	
Ozonbeständigkeit Resistance to Ozone	pass	EN 1844	
Resistance to Hail – soft / hard surface (m/s)	≥ 17		
Resistance to Impact	I10		
Static Puncture (kN)	≥ 0,5		
Hazardous substances	pass		


1) The roof membranes can be used for a Broof(t1) classification for External Fire Performance for a well-defined full roof assembly. Composition of this roof assembly is available upon request.

10. Declaration:

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This Declaration of Performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Sammy Baron



Technical Director
VM Building Solutions NV/SA